

BLR/STAS H48 Replaceable Steel Liquid
And Suction Filter Drier
BLR/STAS H48可拆式液管干燥过滤桶



Technical data / 技术参数

Model 型号	Connection 接口尺寸		CoreQty 滤芯数量	Desiccant Volume 滤芯体积 (cm³)	Dimensions (mm) 尺寸				
	英寸(Inch)	毫米(mm)			A	B	C	D	E
H48 Filter Drier Shells / Single 1节H48过滤芯									
BLR/STAS-485T	5/8 ODF	16	1	48	233	143	80	114	150
BLR/STAS-487T	7/8ODF	22			244	154	90	114	150
BLR/STAS-489T	1 1/8 ODF	28			245	155	92	114	150
BLR/STAS-4811T	1 3/8 ODF	35			243	153	92	114	150
BLR/STAS-4813T	1 5/8 ODF	42			245	164	92	114	150
BLR/STAS-4817T	2 1/8 ODF	54			251	161	100	114	150
BLR/STAS-4821ST	2 5/8 ODF	67			270	157	116	114	150
BLR/STAS-4824ST	3 ODF	76			266	153	116	114	150
BLR/STAS-4825ST	3 1/8 ODF	80			266	152	116	114	150
BLR/STAS-4828ST	3 1/2 ODF	89			273	160	116	114	150
H48 Filter Drier Shells /Double 2节H48过滤芯									
BLR/STAS-967T	7/8 ODF	22	2	96	389	299	90	114	150
BLR/STAS-969T	1 1/8 ODF	28			390	300	92	114	150
BLR/STAS-9611T	1 3/8 ODF	35			388	298	92	114	150
BLR/STAS-9613T	1 5/8 ODF	42			390	300	92	114	150
BLR/STAS-9617T	2 1/8 ODF	54			396	306	100	114	150
BLR/STAS-9621ST	2 5/8 ODF	67			415	302	116	114	150
BLR/STAS-9624ST	3 ODF	76			411	298	116	114	150
BLR/STAS-9625ST	3 1/8 ODF	80			411	321	116	114	150
H48 Filter Drier Shells / Triple 3节H48过滤芯									
BLR/STAS-1449T	1 1/8 ODF	28	3	144	526	436	92	114	150
BLR/STAS-14411T	1 3/8 ODF	35			524	434	92	114	150
BLR/STAS-14413T	1 5/8 ODF	42			526	436	92	114	150
BLR/STAS-14417T	2 1/8 ODF	54			532	442	100	114	150
BLR/STAS-14421ST	2 5/8 ODF	67			551	438	116	114	150
BLR/STAS-14424ST	3 ODF	76			547	434	116	114	150
BLR/STAS-14425ST	3 1/8 ODF	80			547	432	116	114	150
H48 Filter Drier Shells / Quadruple 4节H48过滤芯									
BLR/STAS-19211T	1 3/8 ODF	35	4	192	675	585	92	114	150
BLR/STAS-19213T	1 5/8 ODF	42			677	587	92	114	150
BLR/STAS-19217T	2 1/8 ODF	54			683	593	100	114	150
BLR/STAS-19221ST	2 5/8 ODF	67			702	589	116	114	150
BLR/STAS-19224ST	3 ODF	76			698	585	116	114	150
BLR/STAS-19225ST	3 1/8 ODF	80			698	583	116	114	150

Technical Data

Working Pressure [PS]: 33 Bar
Test Pressure [PT]: 48 Bar
Allowable Temperature [TS]: Min. - 10° C / Max.-130° C
Color[RAL]: 5009
General Tolerans[mm]: ±3

技术参数

工作压力[PS]: 33 Bar
测试压力[PT]: 48 Bar
允许温度[TS]: 最小 - 10° C / 最大-130° C
颜色[RAL]: 5009
一般误差[mm]: ±3

Note:

"T" style means with cooper connection
"ST" style means with steel coonection

注:

"T" 型号表示铜接口
"ST"型号标识铁接口